

## Parafuso Cabeça Sextavada Rosca inteira - A 307

Diam. Rosca (d)	1/4"	5/16"	3/8"	1/2"	1/2"	5/8"	3/4"	7/8"	1"
Rosca / FPP	UNC 20	UNC 18	UNC 16	UNC 13	WW 12	UNC 11	UNC 10	UNC 9	UNC 8
Chave Pol. (S)	7/16"	1/2"	9/16"	3/4"	3/4"	15/16"	1 1/8"	15/16"	1/2"
Chave mm. (S)	11.11	12.70	14.27	19.05	19,05	23.81	28.57	33.33	38.10
Alt. Cab. mm (h)	4.14	5.33	6.17	8.20	8,20	10.23	12.26	14.30	15.92
Comp. Pol. (L)									
1/2"	0,530	0,870	1,290						
5/8"	0,580	0,940	1,400	2,970	2,850				
3/4"	0,620	1,040	1,570	3,250	3,120				
7/8"	0,680	1,100	1,670	3,460	3,320				
1"	0,750	1,240	1,830	3,670	3,560	6,570	10,850		
1 1/4"	0,850	1,420	2,110	4,130	4,010	7,630	11,980		
1 1/2"	0,950	1,590	2,390	4,650	4,510	8,210	13,020	19,150	
1 3/4"	1,090	1,740	2,650	5,190	5,030	8,880	14,150	19,750	
2"	1,170	1,950	2,910	5,660	5,490	9,750	15,340	22,420	31,110
2 1/4"	1,290	2,120	3,200	6,080	5,890	10,560	16,510	23,920	32,800
2 1/2"	1,430	2,310	3,440	6,610	6,410	11,270	17,470	25,550	35,170
2 3/4"	1,580	2,580	3,820	7,180	6,960	12,350	18,630	27,490	37,360
3"	1,640	2,650	4,020	7,620	7,390	12,800	19,700	28,970	39,430
3 1/2"	1,860	3,010	4,550	8,580	8,320	14,410	22,250	32,070	43,410
4"	2,080	3,470	5,090	9,560	9,270	16,150	24,600	34,850	48,150
4 1/2"			5,650	10,590	10,270	17,670	26,770	38,180	51,330
5"				11,550	11,200	19,250	28,920	42,210	55,790
5 1/2"				12,680	12,290	20,660	31,360	45,670	60,420
6"				13,450	13,040	22,400	33,770	47,720	64,660

**Aplicações:** Utilizados em máquinas, equipamentos e outras aplicações.

**Material:** Aço baixo carbono,

**Dimensões:** Conforme ANSI B 18.2.6



**Unidade de Venda:** Kg/CT

