


## Parafuso Sextavado Estrutural - A325 - Rosca Inteira

Diâm. Rosca (d)	3/8"	1/2"	5/8"	3/4"
Rosca / FPP	UNC-16	UNC-13	UNC-11	UNC-10
Chave Pol / mm (S)	11/16 17,47	7/8 22,22	1.1/16 26,98	1.1/4 31,75
Alt. Cabeça mm (h)	6,5	8,2	10,23	12,26
Comp. Pol. (L)				
1"	2,000	4,100	7,300	11,800
1 1/4"	2,300	4,600	8,100	13,000
1 1/2"	2,500	5,100	8,900	14,200
1 3/4"	2,800	5,600	9,700	15,400
2"	3,100	6,100	10,500	16,600
2 1/4"	3,400	6,600	11,400	17,800
2 1/2"	3,700	7,100	12,200	18,900
2 3/4"	4,000	7,600	13,000	20,100
3"	4,200	8,100	13,800	21,300
3 1/4"	4,500	8,600	14,600	22,500
3 1/2"	4,800	9,200	15,400	23,700
3 3/4"	5,100	9,700	16,200	24,900
4"	5,400	10,200	17,000	26,100



**Aplicações:** Alta resistência, utilizado na construção civil, montagens de estruturas metálicas, montagens industriais, torres de transmissão de energia, etc.

**Material:** Aço médio carbono temperado e revenido.

**Unidade de Venda:** Kg/CT