


Parafuso Sextavado Estrutural - A394

| Diâm. Rosca (d) | 1/2" | 5/8" | 3/4" | 7/8" | 1" |
|-------------------|--------|--------|--------|---------|--------|
| Rosca / FPP | 13 UNC | 11 UNC | 10 UNC | 9 UNC | 8 UNC |
| Chave Pol. (S) | 3/4" | 15/16" | 1 1/8" | 1 5/16" | 1 1/2" |
| Alt. Cab. mm (h) | 7,70 | 9,60 | 11,55 | 13,50 | 15,01 |
| Comp. Ros. mm (b) | 26,00 | 29,00 | 31,50 | 34,00 | 37,00 |
| Comp. Pol. (L) | | | | | |
| 1 1/4" | 4,517 | 7,885 | | | |
| 1 1/2" | 4,864 | 8,346 | 12,975 | 20,700 | 31,800 |
| 1 3/4" | 5,493 | 9,406 | 14,409 | 22,400 | 33,900 |
| 2" | 6,052 | 10,301 | 16,142 | 24,100 | 36,000 |
| 2 1/4" | 6,712 | 11,371 | 17,120 | 25,270 | 38,200 |
| 2 1/2" | 7,410 | 12,301 | 18,676 | 27,500 | 40,600 |
| 2 3/4" | 8,197 | 13,274 | 19,976 | 29,300 | 43,000 |
| 3" | 9,100 | 14,254 | 21,323 | 31,200 | 41,910 |
| 3 1/4" | 9,700 | 15,700 | 23,102 | 33,100 | 48,000 |
| 3 1/2" | 10,350 | 16,700 | 24,203 | 35,100 | 50,200 |
| 3 3/4" | 11,000 | 17,600 | 25,885 | 36,900 | 53,000 |
| 4" | 11,600 | 18,600 | 27,800 | 38,800 | 55,200 |
| 4 1/4" | 12,200 | 19,600 | 29,100 | 40,600 | 57,500 |
| 4 1/2" | 12,800 | 20,500 | 30,500 | 42,500 | 60,200 |
| 4 3/4" | 13,400 | 21,400 | 31,800 | 44,300 | 62,500 |
| 5" | 14,100 | 22,400 | 33,200 | 46,200 | 63,500 |
| 5 1/4" | 14,800 | 23,400 | 34,600 | 48,500 | 64,800 |
| 5 1/2" | 15,500 | 24,300 | 36,000 | 50,200 | 67,700 |
| 5 3/4" | 16,200 | 25,200 | 37,400 | 52,100 | 70,000 |
| 6" | 16,900 | 26,100 | 38,700 | 54,000 | 72,500 |



Aplicações: utilizado na construção civil, montagens de estruturas metálicas, montagens industriais, torres de transmissão de energia, etc.

Material: Aço baixo carbono.
(obs: acab. galvanizado à fogo)

Unidade de Venda: Kg/CT

Dimensões: Conforme ANSI B 18.2.6