

Estojo ASTM A-193-B7 sem porca

ESTOJO										
Diâm. Pol (d)	3/8"	1/2"	5/8"	3/4"	7/8"	1"	1 1/8"	1 1/4"	1 1/2"	1 3/4"
	UNC 16	UNC 13	UNC 11	UNC 10	UNC 9	UNC 8	UN 8	UN 8	UN 8	UN 8
Comp. Pol (L)										
1 1/2"	1,700	3,090								
2"	2,260	4,050	6,330	9,660	12,877					
2 1/2"	2,820	5,060	7,910	12,070	16,097					
3"	3,390	6,070	9,490	14,480	19,317	25,199	32,301			
3 1/2"	3,950	7,080	11,070	16,900	22,536	29,399	37,685	47,330		
4"	4,520	8,090	12,650	19,310	25,756	33,599	43,068	54,092	79,644	104,546
4 1/2"	5,080	9,100	14,230	21,720	28,975	37,799	48,452	60,853	89,600	117,615
5"	5,640	10,110	15,820	24,130	32,195	41,999	53,835	67,615	99,553	130,683
5 1/2"	6,210	11,120	17,400	26,550	35,414	46,199	59,219	74,376	109,511	143,751
6"	6,770	12,140	18,980	28,960	38,633	50,399	64,602	81,138	119,466	156,820
6 1/2"	7,330	13,150	20,560	31,370	41,853	54,599	69,986	87,899	129,422	169,888
7"	7,900	14,160	22,140	33,790	47,072	58,798	75,369	94,661	139,377	182,956
7 1/2"	8,460	15,170	23,720	36,200	48,292	62,998	80,753	101,42	149,333	196,025
8"	9,030	16,180	25,300	38,610	51,511	67,198	86,136	108,184	159,288	209,093
8 1/2"	9,590	17,190	26,880	41,030	54,731	71,398	91,520	114,945	169,440	222,161
9"	10,170	18,220	28,500	43,500	58,026	75,697	97,031	121,866	179,435	235,538
9 1/2"	10,720	19,210	30,050	45,850	61,176	79,798	102,287	128,468	189,155	248,298
10"	11,280	20,220	31,630	48,260	64,389	83,998	107,670	135,230	199,110	261,366

Aplicações: Utilizado em montagens industriais, válvulas, conexões, flanges e aplicações diversas.

Material: Aço liga, temperado e revenido

Dimensões: Conforme ANSI 16,5
Tratamentos superficiais diversos

Unidade de Venda: Kg/Ct

