


Parafuso Cabeça Chata com Sextavado Interno Polegada Inox 304

Diâmetro Rosca (d)	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"
Rosca / FPP	UNC 24	UNC 20	UNC 18	UNC 16	UNC 13	UNC 11	UNC 10
Chave Pol / mm (S)	1/8"-3,17	5/32"-3,96	3/16"-4,76	7/32"-5,55	5/16"-7,93	3/8"-9,52	1/2"-12,70
Alt. Cabeça mm (h)	3,22	4,09	5,02	5,94	6,37	8,22	10,05
Diâm. Cab mm (D)	9,11	12,19	15,24	18,28	22,14	28,24	34,41
Comp. Rosca mm (b)	22,22	25,40	28,44	31,75	38,10	44,45	50,80
Comp. Polegada (L)							
1/4"							
3/8"							
1/2"	0,200	0,390					
5/8"	0,240	0,450	0,760				
3/4"	0,270	0,510	0,850	1,310			
1"	0,340	0,630	1,050	1,590	2,670		
1 1/4"	0,400	0,750	1,240	1,870	3,180	5,397	8,011
1 1/2"	0,510	0,870	1,430	2,150	3,690	5,988	9,204
1 3/4"		1,050	1,620	2,430	4,200	6,579	10,282
2"		1,170	1,940	2,710	4,710	7,331	11,220
2 1/4"				3,170	5,220	8,348	12,584
2 1/2"				3,460	6,000	9,100	13,640
3"				4,150	7,030	10,605	15,975



Unidade de Venda: Kg/CT