


Rosca Máquina Cabeça Panela com Fenda Phillips DIN 7985

Diâmetro (d)	M 2	M 2,5	M 3	M 4	M 5	M 6	M 8
Passo	MA-0,4	MA-0,45	MA-0,5	MA-0,7	MA-0,8	MA-1,00	MA-1,25
Diam. Cab. mm (D)	4,0	5,0	6,0	8,0	10,0	12,0	16,0
Alt. Cabeça mm (h)	1,6	2,12	2,52	3,25	3,95	4,75	6,0
Chave PHS nº	1	1	1	2	2	3	4
Comp. mm (L)							
6	0,021	0,038	0,061	0,128			
8	0,024	0,043	0,071	0,136			
10	0,028	0,047	0,078	0,144	0,276	0,428	
12	0,031	0,057	0,085	0,166	0,308	0,478	
16		0,067	0,104	0,196	0,351	0,554	
20		0,080	0,119	0,23	0,387	0,597	1,320
25			0,138	0,267	0,453	0,712	1,480
30			0,158	0,302	0,506	0,76	1,640
35				0,332	0,572	0,886	1,800
40				0,370	0,637	0,951	1,960
45				0,413	0,697	1,034	2,120
50				0,455	0,753	1,126	2,280
60					0,890	1,300	2,600
70						1,450	2,970
80						1,633	3,390
90							3,880
100							4,440



Unidade de Venda: Kg/CT